

WP410 is a basic VoIP desk phone, perfect as an unattended phone for calling.

WP410 HIGHLIGHTS

- | | |
|------------------------|-----------------------|
| • Display: 132*64 LCD | • Call history sync |
| • 2 x Port 10/100 | • Quick DND key |
| • PBX phonebooks | • VM notification |
| • 4 BLF keys (2 pages) | • Visual / audio BLF |
| • PoE IEEE 802.3af | • Presence monitoring |



TECH SPECIFICATIONS

Phone & PBX

- | | |
|---|---|
| • Presence | Intercom, paging, speed dial, hold, 3-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold |
| • New Voicemail / Missed call / New call notification | |
| • Online access to PBX phonebooks | |
| • Sync of call history and missed call notifications | • Multi-language support |
| • PBX ringtones | |

Audio

- | | |
|--|-----------------------|
| • Narrowband codec G.711a, ulaw, G.729 | • Full-duplex speaker |
| | • Echo canceller |

Security & Networking

- SIP TLS; QoS VLAN; RTP/RTCP

Physical

- | | |
|--|--|
| • WP410: 4 BLF (software keys) | •PoE IEEE 802.3af WP410: PoE class 1 |
| • WP410: 2.3” display with backlight 132*64 | •WP410: 2 x RJ45 10/100 Mb Ethernet ports |
| • 1 x RJ9 headset port; 1 x RJ9 handset port | •Giftbox size & weight: WP410 207*197*102 mm, 0.8 kg; |
| • Optional Power Adapter: Input AC 100-240 V; Ouput DC 5V / 1A | •Operating t°: 32~104 °F, 0~40 °C; Storage t°: 14~122 °F, -10 ~ 50 °C; Humidity: 10 to 90 % Non-condensing |
| • Max power consumption: WP410: 1.3W | |